

PUBLIC VIEW MONITORS

EXTRA-LARGE FORMAT

FEATURES

- HD Video Provides Exceptional Viewing and Forensic Details
- Attention Grabbing Features Deliver High-Deterrent Value (Face Block and Flashing LED's)
- Low Voltage for Simple and Cost-Effective Deployments
- 3 Built-in Camera Extension Ports Adds Cost-Effective Display and Surveillance Options
- Video Motion Detection
- White LEDs (On, Off, Flashing, Motion On, Motion Flash)



MODEL NUMBER	APVM32-B-AFA51-B	APVM43-B-AFA51-B	APVM55-B-AFA51-B
DISPLAY			
Panel	32" LED Backlight	43" LED Backlight	55" LED Backlight
Resolution	1920 x 1080 (1080p)	3840 x 2160 (4K)	3840 x 2160 (4K)
Contrast Ratio	3000:1	1000:1	1200:1
Response Time	18 ms	8 ms	8 ms
CABINET			
VESA Pattern	200 x 100	200 x 200	400 x 200
Dimensions - W x H x D (in)	29.29 x 17.44 x 2.01 (in) 744 x 443 x 51 (mm)	38.11 x 22.17 x 3.19 (in) 968 x 563 x 81 (mm)	49.17 x 28.54 x 3.58 (in) 1249 x 725 x 91 (mm)
Weight	27.8 lbs (12.6 kg)	32.2 lbs (14.6 kg)	47.8 lbs (21.7 kg)
CONNECTIONS / POWER			
Power Consumption	60 Watts	72 Watts	240 Watts

ACCESSORIES

- MMB0302** Articulating Wall Mount, VESA 75x200, Black
- MMB0601** Ceiling Mount, Back-to-Back, 1.5" NPT, VESA 400x400 Black (w/ CM-XL-x Pole)
- MMB0602** Ceiling Mount, Single, 1.5" NPT, VESA 400x400, Black (w/ CM-XL-x Pole)
- MMB0603** Ceiling Mount, Single, 1.5" NPT, VESA 75-200, Black (w/ CM-XL-x Pole)
- MMB0604** Ceiling Mount, Back-to-Back, 1.5" NPT, VESA 75-200, Black (w/ CM-XL-x Pole)
- CM-XL-5-W** Telescoping Pole, 2-5.5' length, White (w/ MMB060x Ceiling Mount)
- CM-XL-11-W** Telescoping Pole, 6-11' length, White (w/MMB060x Ceiling Mount)
- CM-XL2-21-W** Telescoping Pole, 8-21' length, White (w/ MMB060x Ceiling Mount)
- DCSP-CMXL** Drop Ceiling Support Plate, use with a CM-XL-x Pole, White
- CS-7** Unistrut, 7', Open Ceiling Framing Channel, White

MODEL NUMBER	Various*
DISPLAY	
Aspect Ratio	16:9
CAMERA	
Camera Type	Axis FA54 with FA1105 Sensor
Resolution	2MP, 1920 x 1080
Minimum Illumination	0.02 Lux
Lens	2.8 mm F2.0
Shutter Speed	1/32500 sec. – 1/30 sec. w/ 60 Hz
Video Format	H.264, MJPEG
CABINET	
Construction	Black Plastic
Operating Temperature	-4°F - 140°F (-20°C - 60°C)
CONNECTIONS / POWER	
Input Voltage	24VDC
Network	1 RJ45
HDMI	2 Inputs

CERTIFICATIONS

UL, CE, FCC Class B RoHS Compliant

DISPLAY EXTRAS - PVM43- B-1001-B

- BRIGHTNESS** 300 NIT
- VIEWING ANGLES** 178° x 178° (W x H)

*MODELS INCLUDED IN CHART -
APVM32-B-AFA51-B, APVM43-B-AFA51-B, APVM55-B-AFA51-B