

PUBLIC VIEW MONITOR

10" CORRIDOR IP

FEATURES

- Captures Top-to-Bottom Views - Great for POS Areas and Narrow Aisles
- HD Video Provides Exceptional Viewing and Forensic Details
- Attention Grabbing Features Deliver High-Deterrent Value
- Low Voltage for Simple and Cost-Effective Deployments
- UL Listed
- PoE or DC Powered



SPECIAL FEATURES

- VMS-based Video Recording Via Network
- Corridor Format Allows for Greater Vertical Field of View
- Text Overlay "Recording In Progress" or "Welcome" Messages
- Flashing or Continuous Blue LED, Front Panel White LEDs (On, Off, Flashing, Motion Activated)
- Video Motion Detection, Audio Alert and/or Front Panel White LEDs After Motion Detection
- Comes with Remote Control
- Firmware Upgrade via SD Card
- Customer Logo and Audio Clips Loadable via SD Card
- Camera Defeat Alarm
- Face Detection Boxes (Neon Green, Front and Side Detection)
- Auto-on

MODEL NUMBER	PVM10-B-2086-W
Display	10" LED Backlight
Resolution	1280 x 800
Aspect Ratio	16:9
Brightness	250 NIT
Contrast Ratio	800:1
Viewing Angle - W x H	170° x 170°
Response Time	30 ms
VESA Pattern	75 x 75
Dimensions - W x H x D (in)	7.50 x 11.38 x 1.38 (in)
Weight	4.0 lbs (1.8 kg)
Construction	White Steel w/ Glass Front
Operating Temperatures	32°F - 104°F (0°C - 40°C)
Image Sensor	1/2.9" Sony IMX323

MODEL NUMBER	PVM10-B-2086-W
Camera Resolution	1080p
Effective Pixels	1985 (H) x 1105 (V), 2.19 MP
Minimum Illumination	0.01 Lux / F1.2
Lens	3.3 mm fixed
Shutter Speed	1/60–1/10,000 second
Certifications	UL, FCC, RoHs
Video Format	H.264
S/N Ratio	39 dB
Compatibility	Vivotek, ONVIF
Input Voltage	PoE 802.3af or 12V DC
SD Card	OSD, Firmware & LOGO
Network	RJ45
Digital Output	2 Spring Terminals

ACCESSORIES

MMB0303	Monitor Mount, Wall, Articulating, VESA 75x100, Black
MM-PVM08GUX-W	Monitor Mount, Retail Gondala Uprights, VESA 75x75, White
MM-PVM08CWA-W	Monitor Mount, Retail Display Walls, VESA 75x75, White
MM-PVM07SCO-W	Monitor Mount, Self Checkout Power Pole Mount, VESA 75x75, White
CM-S10-8-W	Ceiling Mount, Telescoping, Single, 5-8' length, VESA 75x75, White
CM-S10-17-W	Ceiling Mount, Telescoping, Single, 8-17' length, VESA 75x75, White
CM-S10-27-W	Ceiling Mount, Telescoping, Single, 10-27' length, VESA 75x75, White
CM-BB10-8-W	Ceiling Mount, Telescoping, Back-to-Back, 5-8' length, VESA 75x75, White
CM-BB10-2-17-W	Ceiling Mount, Telescoping, Back-to-Back, 8-17' length, VESA 75x75, White
CM-BB10-27-W	Ceiling Mount, Telescoping, Back-to-Back, 10-27' length, VESA 75x75, White
DCSP-CMSBB10	Drop Ceiling Support Plate, use with a CM-BB10-x or CM-S10-x-pole
CS-7	Unistrut, 7', Open Ceiling Framing Channel, White
PS-10PVM	Power Supply, Brick, 12VDC, 4A